

## AMENDMENTS TO THE SPECIFICATION

**Please replace paragraph [0023] with the following amended paragraph:**

[0023] The frame comprises an outer channel member (18), an inner channel member (20) and dual intermediate web members (22) which join the inner and outer channel members. [...] The inner channel member may include an installation flange (24) which projects outwardly and will abut a window jamb (not shown) when installed into a wall frame. A removable desiccant concealing member (26) is attached to the inner channel member (20) opposite the installation flange (24) which serves to retain the glass unit but does not serve any other structural function. The desiccant concealing member (26) is tube-shaped defining a single elongate channel (28). One edge of the channel defines a first lip (30) while the other edge of the channel defines a second lip (32). The two lips (30, 32) mate with corresponding grooves (31, 33) formed in the inner channel member (20).

**Please replace paragraphs [0025] and [0026] with the following amended paragraphs:**

[0025] In a preferred embodiment, a dual desiccant system is employed. The spacer is a hollow rectangular member which is filled with a suitable desiccant (40). The spacer defines pores which allow air to circulate between the air space between the glass panes (10, 12) and the interior volume of the spacer which contains the desiccant. As well, a small conduit (42) connects the interior space of the spacer to a sealed tube (44) within the desiccant concealing member (26) which is filled with desiccant (40). The sealed tube ~~(40)-(44)~~ has a cap (46) which receives the conduit (42) thereby providing gas communication between the spacer interior volume and the desiccant tube (44).

[0026] As is apparent, the desiccant concealing member (26) may be removed from the frame (14) by disengaging the lips (30, 32) from the inner channel member (20), thereby exposing the desiccant tube (44). The desiccant tube (44) can then be easily disconnected from the conduit ~~(44)-(42)~~ and replaced with a fresh desiccant tube if necessary. In one alternative embodiment, the desiccant in the desiccant tube may be different from the desiccant contained in the spacer and has a higher affinity for water than the desiccant in the

spacer. As will be appreciated by those skilled in the art, air which is drawn into the air space must pass through the replaceable desiccant tube, thereby preserving the dry atmosphere within the window unit.